



Westinghouse

INNOVATION YOU CAN BE SURE OF

2400i

Digital Inverter Generator

Westinghouse digital inverter generators offer you the ultimate in portable power convenience. Lightweight, fuel efficient and quiet, their mains-quality electrical output can safely power all of your sensitive electronic equipment. They're an essential part of your gear for caravanning and camping and also great for home as a backup power supply.

Features and Benefits

Powerful

2,400 Watts maximum output is the highest in its class to run more of your electrical devices.

Lightweight

At only 20 kg it can be easily carried by one person using the ergonomic non-slip handle.

Quiet

Ultra-silent running from only 51 dB(A) that won't disturb you or your neighbours.

Long Running

Up to 24 hours achieved by its fuel-efficient engine and biggest-in-class 5 L fuel tank.

Easy To Use

Yellow-coloured touch points guide you to the controls required for normal operation.

Mains Quality Electricity

Digital inverter technology safely powers all of your sensitive electronic equipment.

Clean Air Technology

4-stroke OHV petrol engine with Australian and US EPA compliant emission controls.

Plug and Play

Everything you need is in the box. No assembly required. Just add petrol.

Safety Protection

Electrical overload circuit breaker and low engine oil shutdown safeguards.

Warranty Protection

2-year domestic use warranty to safeguard your investment (conditions apply).

2100 / 2400

RUNNING WATTS STARTING WATTS



Control Panel Functions



Power - when you need it - where you need it

Specifications

2400i

ENGINE		240 VOLT AC ELECTRICAL	
Type	1-Cylinder, 4-Stroke, Overhead Valve, Air Cooled	Voltage (V)	240
Displacement (cc)	79	Frequency (Hz)	50
Maximum Speed (rpm)	5,000	Number of Phases	1
Oil Capacity (mL)	400	Continuous Running Power (W) *	2,100
Low Oil Shutdown	Yes	Maximum Starting Power (W)	2,400
Spark Plug	Torch A5RTC	Continuous Running Current (A)	8.8
Fuel	Unleaded Petrol	Voltage & Waveform Control	Digital Inverter, Pure Sine Wave Output
Fuel Tank Capacity (L)	5.0	Total Harmonic Distortion (THD)	< 2.5%
Auto-Speed ECO Throttle	Yes	Receptacles	2 x 15 A, IP44
Fuel Gauge	Yes	Overload Protection	Electronic
Auto-Speed ECO Throttle	Yes	Alternator	Brushless, Permanent Magnet
Starting Method	Recoil	Output Meter	Digital, Multi-Function
Hour Meter	Yes	DIMENSIONS	
Run Time @ 400 / 1,600 W	16 / 5 hours	Length (mm)	500
Noise Level @ 400 / 1,600 W	52 / 61 dB(A) @ 7m	Width (mm)	340
12 VOLT DC ELECTRICAL		Height (mm)	440
Voltage (V)	12	WEIGHT	
Maximum Current (A)	8	Weight - Dry (kg)	20
Maximum Power (W)	100	Weight - Wet (kg)	24
Receptacle	8 A, IP44	* Rated output at 1.0 power factor.	

