



Westinghouse

INNOVATION YOU CAN BE SURE OF

iGen2600

Digital Inverter Generator

Westinghouse digital inverter generators offer you the ultimate in portable power convenience. Lightweight, fuel efficient and quiet, their mains-quality electrical output can safely power all of your sensitive electronic equipment. They're an essential part of your gear for caravanning and camping and also great for home as a backup power supply.

Features and Benefits

Powerful

2,600 Watts maximum output is the highest in its class to run more of your electrical devices.

Lightweight

At only 22.5 kg it can be easily carried by one person using the ergonomic non-slip handle.

Quiet

Ultra-silent running from only 52 dB(A) that won't disturb you or your neighbours.

Long Running

Up to 19 hours achieved by its fuel-efficient engine and long range 5 litre fuel tank.

Easy To Use

Yellow-coloured touch points guide you to the controls required for normal operation.

Mains Quality Electricity

Digital inverter technology safely powers all of your sensitive electronic equipment.

Clean Air Technology

4-stroke OHV petrol engine with Australian and US EPA compliant emission controls.

Plug and Play

Everything you need is in the box. No assembly required. Just add petrol.

Safety Protection

Electrical overload circuit breaker and low engine oil shutdown safeguards.

Warranty Protection

2-year domestic use warranty to safeguard your investment (conditions apply).

2200/2600

RUNNING WATTS STARTING WATTS



PURE SINE WAVE

Control Panel Functions

240-Volt AC, 15-Amp Outlets with Covers

Low Oil Alarm safeguards engine

Overload Alarm requires operator attention

Output Indicator shows AC power available

Fuel Level Bar Gauge

Data Center



ECO Throttle Control to minimise fuel consumption

Frame Terminal for earthing

Output Power Level Bar Gauge



Power - when you need it - where you need it

Specifications

iGen2600

ENGINE	
Type	1-Cylinder, 4-Stroke, Overhead Valve, Air Cooled
Displacement (cc)	98
Maximum Speed (rpm)	5,000
Oil Capacity (mL)	350
Low Oil Shutdown	Yes
Spark Plug	Torch E6RTC
Fuel	Unleaded Petrol
Fuel Tank Capacity (L)	5.0
Fuel Gauge	Yes #
Auto-Speed ECO Throttle	Yes
Starting Method	Recoil
Hour Meter	Yes #
Run Time @ 450 / 1,800 W	11 / 5.5 hours
Noise Level @ 400 / 1,600 W	52 / 61 dB(A) @ 7m

DIMENSIONS	
Length (mm)	550
Width (mm)	310
Height (mm)	480

240 VOLT AC ELECTRICAL	
Voltage (V)	240
Frequency (Hz)	50
Number of Phases	1
Continuous Running Power (W) *	2,200
Maximum Starting Power (W)	2,600
Continuous Running Current (A)	9.2
Voltage & Waveform Control	Digital Inverter, Pure Sine Wave Output
Total Harmonic Distortion (THD)	< 2.5%
Receptacle	2 x 15 A, IP44
Overload Protection	Electronic
Alternator	Brushless, Permanent Magnet
Output Power Meter	Yes #

WEIGHT	
Weight - Dry (kg)	22.5
Weight - Wet (kg)	26.5

* Rated output at 1.0 power factor. # Data Center display.

